

SDC 8200 is the solution you are looking for. Fully digital, the system sets new standards in professional conference technology. SDC 8200 is a flexible communications solution – a sound investment that pays off, again and again. SDC 8200 is available in a number of variants catering to different needs. Regardless of requirements – whether you are hosting a small conference or a large congress – there is always a suitable SDC system for your application.



SDC 8200 D

The basic version of the SDC delegate unit features a gooseneck microphone, built-in loudspeaker, two headphone jacks with individual volume controls, MIC key, LED status display, and three voting keys (yes, abstain, no).

SDC 8200 C

The basic version of the chairman's unit incorporates the same features as the SDC 8200 D delegate unit plus two special keys for switching off live microphones (priority key) and for activating the microphone of the next participant who would like to speak (when in Request mode).

- "Request to speak" LED
- Mic on/off LED
- Headphone volume controls (on both sides)
- Three voting keys with LEDs

Technical Data	SDC 8200 D/SDC 8200 C
Cat. No.	500863/500858
Audio frequency response	100 – 14,000 Hz
Microphone pick-up pattern	cardioid
Headphone jack(s)	3.5 mm mono ($\geq 32 \Omega$)
Operating voltage	48 V DC
Power consumption	max 2.5 W
Operating temperature range	+5 °C to +50 °C
Finish	Pantone Black 7
Housing	ABS
Dimensions (mm)	150 x 80 x 185
Length of gooseneck (mm)	380
Weight	560 g
Connectors	2 x RJ 45 jacks for connecting up to 20 units in one cable line

Accessories	Product	Cat. No.
conference bus cables, type 24 AWG, available lengths: 2, 3, 5, 10, 20, 50 m (Please note: Do not use standard Ethernet AWG 26 cables!)	SDC CBL RJ45-2	009842
	SDC CBL RJ45-3	009843
	SDC CBL RJ45-5	009844
	SDC CBL RJ45-10	009845
	SDC CBL RJ45-20	009846
Headphones	SDC CBL RJ45-50	009847
	HD 410 D	002146
	HD 1029	003985