Digital Conference and Interpretation System SDC 8200 CU/CU-M Communication across boundaries

SDC 8200 is the solution you are looking for. Fully digital, the system sets new standards in professional conference technology. SDC 8200 is a flexible communications solution – a sound investment that pays off, again and again. SDC 8200 is available in a number of variants catering to different needs. Regardless of requirements – whether you are hosting a small conference or a large congress – there is always a suitable SDC system for your application.

	ISER	ir
ô		



Technical Data	SDC 8200 CU	SDC 8200 CU-M
Cat. No.	500867	500860
Max. number of conference terminals	120	50
Can be used with SDC 8200 DV	yes	no
Cascadable	yes (system max.: 1024 conference terminals)	no
Language channels	4/8/28 (depen- ding on licence)	4
Interpreter units per language	1 to 8	2
Supported voting modes	one out of three, one out of five	one out of three
Camera and media control	yes	yes
Connection of SDC 8200 AO	up to 4	no
Control software	SDC 8200 SYS	SDC 8200 SYS-M

SDC 8200 CU/CU-M

The heart of every system. These central units feature a host of control functions plus all the connection sockets required for the delegate units, additional audio sources, monitoring headphones, PC, interpretation management and camera control. While the SDC 8200 CU is the ideal choice for large international conferences with many hundreds of delegates (several CU can be connected together for very large systems), the SDC 8200 CU-M has been designed for smaller applications; it has a limit of 50 terminals and four interpreted language channels with a maximum of two interpreter units per language.

- Wheel for menu selection
- COM 1 to COM 3 serial interfaces for PC and media control

10/06

